

The Hopper  
MET 494 Senior Design  
Alexander Heine, Patrick LaRoy, Kyle Macke, Jedd Minnich



## **Purpose & Function:**

The objective of this project is to improve the method of how ferromanganese is distributed to molten steel at Steel Dynamics Butler, Indiana at their melting facility. When ferromanganese is added it acts as an alloying agent improving the quality of the steel. The current process is neither cost effective nor efficient use of time. SDI purchases ferromanganese in 25-pound bags and empties individual bags into a wheel-barrel then pours into a kiln. The main categories that were focused on for the design include a large industrial hopper, rotating paddle assembly, and a conveyor.

SDI currently owns four large industrial hoppers that can volumetrically hold 4000-6000 lbs. of ferromanganese. Previously the hoppers held lime mineral, as this material is added to molten steel to take out any impurities from scrap steel they receive. The hopper is located on the south end of the melting furnace. SDI found a new method to place lime into the melting furnaces and the hoppers were abandoned. This was a critical aspect of the project as the volumetric capacity of the hopper was calculated with reference to the density of ferromanganese. The bottom section of the hopper will be removed and replaced with the paddle assembly.

The paddle assembly took several weeks to be approved by SDI's engineers. Throughout the design process there were five individual design changes occurred to ensure durability. The housing for this design includes two plates that are welded to a rotary shaft that will be placed in a cylindrical outer casing. The assembly will be ran by a low horsepower and high torque motor that will be attached to the hopper but located outside of the frame in case any maintenance is required. A36 steel was chosen for this particular section as it has durable metallurgic properties such as shear and ultimate tensile strength. The ferromanganese will be dumped into each of the four compartments as the paddles rotate 360 degrees.

As mentioned in the paragraph above the motor used to rotate the paddle assembly will have low horsepower and high torque. The motor is currently attached to the hopper and was cost effective to keep and continue to use it. A gear reducer was required for the paddle assembly, as each rotation needed an immediate stopping mechanism to ensure there was no extra material that will be pouring outside of the 26" wide conveyor. The reducer used will have a 100:1 gear ratio that SDI current has from previous projects. The force of ferromanganese in the hopper will stop spinning the paddle around after the cycle is complete.

A drag chain conveyor was designed and purchased through Enduraveyor. The original hopper has a set of angle iron tracks that it road o with a small motor to bring the hopper up and dispense the material. The current iron tracks are getting cut back, and the conveyor will be attached to the hopper. The conveyor has four caster attached to the bottom that will allow it to be moved easily. Since steel dynamics equipment is susceptible to a harsh environment, the conveyor was designed to be robust and preferably all steel. The weight of the ferromanganese dropping down onto the conveyor was incorporated by changing the plate to hardened steel and making it replaceable. The hardened steel plate will last longer, and have better wear resistance.

**Initial Performance & specifications:**

The overall aspect for this project was to have an efficient and robust system to withstand the harsh environment of the steel mill. The use of 25-pound bags was eliminated and SDI can now purchase 4000-pound super sacks, which are the main contribution to cost savings. The material will be loaded by forklifts or an overhead crane and will be dumped into the hopper. The conveyor will turn on first then the paddle assembly will start to rotate. A PLC program was written to run the entire process. Once the paddles rotate 360 degrees, the paddles will stop moving while the conveyor keeps running to deliver the load. The conveyor will move 30 ft. /minute. SDI will be installing all equipment and running tests on the system, the lead-time for this project did not leave enough time to run an initial performance.

**Design Calculations:**

**Figure 1:**

<b>Volumetric Calculations</b>	
<b>Paddle Volume</b>	
<b>Two Paddle</b>	
$(11.5\text{in} \times 11.375\text{in} \times .5\text{in}) + (11\text{in} \times 11.375\text{in} \times .5\text{in}) = 127.969 \text{ in}^3$	
<b>Four Wear Bars</b>	
$(1.75\text{in}^2 \times 11.375\text{in}) \times 4 = 79.625 \text{ in}^3$	
<b>Total Volume</b>	
$79.625\text{in}^3 + 127.969\text{in}^3 = 207.594 \text{ in}^3$	
<b>Housing Volume</b>	
$((12.5 \text{ in})^2 \times \pi) / 4 \times 11.375 \text{ in} = 1395.923 \text{ in}^3$	
<b>Total Volume</b>	
Total Volume = Housing Volume - Paddle Volume	
$1395.923 \text{ in}^3 - 207.594 \text{ in}^3 = 1188.329 \text{ in}^3$	
<b>Volumetric Weight Calculation</b>	
Total weight of material through one full rotation	
density of ferromanganese = 249.72 lb/ft <sup>3</sup>	
$1188.329 \text{ in}^3 / 1728 \text{ in}^3 = 0.688 \text{ ft}^3$	
$.688 \text{ ft}^3 \times 249.72 \text{ lb/ft}^3 =$	<b>171.730 lb</b> <b>Total Weight</b>

Figure 2:

<b>Net Torque = T1 - (T2+Tm)</b>
$T_m = 70 \text{ \# ft.} * (5.75 \text{ in} * (1/12 \text{ in})) = 33.54 \text{ ft. \#}$
<b>4000 lb Torques</b>
$T_1 = 4000\# * 5.75\text{in} = 23,000 \text{ in \#} = 1916.67 \text{ ft. lb.}$
$T_2 = [ 4000\# ( \sin(135) ) * 5.75 \text{ in} = 16,263.46 \text{ in \#} = 1355.29 \text{ ft. \#}$
<b>Tnet( 4000 \# ) : 1916.67 ft. \# - ( 1355.29 ft \# + 33.54 ft \# ) = 527.84 ft \# CCW</b>
<b>500 lb Torques</b>
$T_1 = 500\# * 5.75 \text{ in} = 2875 \text{ in \#} = 239.58 \text{ ft. \#}$
$T_2 = [ 500\# * ( \sin(135) ) * 5.75 \text{ in} = 2032.93 \text{ in \#} = 169.41 \text{ ft. \#}$
<b>Tnet( 500 \# ) : 239.58 ft. \# - ( 169.41\# + 33.54\# ) = 36.63 ft. \# CCW</b>

**Diagrams & Formal Engineering Drawings:**

See attached PDF File.

**Photographs & Components**

Figure 3:



- Bottom half of current hopper will be replaced with paddle assembly as seen in final detail drawings.

**Figure 4:**



- Ferromanganese will be brought from the hopper, to the conveyor system, the entrance to the kiln is pictured above.

**Figure 5:**



- Current rail system will be cut down to allow maintenance equipment to flow through area. This is also where our conveyor will be placed to bring it to the kiln.

**Fabrication Procedure:**

All of the rotary fabrication will be done in house in steel dynamics fabrication shop. The bottom section of the hopper will be completely removed as shown in fig 3 and will be placed in the scrap metal to be melted. A 9 ft. section of the rail system will be removed to make room for the conveyor system and will be utilized elsewhere in the facility. The rotating paddle assembly will be worked on through SDI's fabrication shop as it requires several welds and current materials they already have in inventory. Enduraveyor will be manufacturing the conveyor through their fabrication shop and approximately take 3-6 weeks of lead-time until it is completed. After all fabrications have been implemented testing will begin for efficiency and references from employees.

**Test Results:**

The conveyor lead-time set back the design from having any tests ran on the system. The lead-time to manufacture the conveyor will take approximately 5 weeks. With the paddle assembly manufactured through SDI's fabrication shop will approximately take 2-3 weeks. The project will be completed and tested during May 1<sup>st</sup> – 7<sup>th</sup> as the outage week allows time for implementation. The engineers approved our design and would like us to make additional modifications for the rotary portion of the project to fit on their additional 3 hoppers.

**Overall Costs:**

The chart below represents the overall cost of the project and the annual cost savings per year after the system has been installed. Ferromanganese is the most cost effective section for this project as buying in bulk has reduced the price savings of \$0.20 per pound. This estimation includes one outage week (7 days) and a down day for maintenance every other Wednesday of the month (25 days) throughout the entire working year. The information received from the reduced labor cost was provided by SDI for every down day if maintenance is required the time will be devoted to this.

**Figure 6:**

<b>Cost Benefit Analysis</b>	
<b>Cost</b>	
<b>Item</b>	<b>Cost</b>
Conveyor	\$8,936.00
Paddle Wheel Assembly	\$500.00
Hopper Modification	\$300.00
Labor	\$1,500.00
Down time (loss)	\$1,000.00
<b>Total Cost</b>	<b>\$12,236.00</b>
<b>Benefits (estimated for first year of use)</b>	
Reduced labor cost	\$6,200.00
Bulk Price cost savings	\$371,280.00
<b>Total Benefits</b>	<b>\$377,480.00</b>

**Bibliography:**


- Eramet. Manganese Alloys, HCFeMN: High carbon ferromanganese, version 1, Eramet Company, 01/01/2017, Paris, France. <http://www.eramet.com/en/our-activities/extracting-generating-value/manganese/our-products/hcfemn-high-carbon-ferromanganese>
- Enduraveyor. Conveyors, Drag Chain Conveyors, Complete Drives Inc., 01/01/2014, Auburn, Indiana. <http://www.endura-veyor.com> “Complete Drive Inc.”
- Grove Gear. Worm Gear Reducers, Cast Iron (GR Series), 04/01/2017, Grove Gear Inc., Union Grove, Wisconsin. <http://www.grovetgear.com/products/worm-gear-reducers/gr/>
- McMaster-Carr. Products, Measuring & Inspection, 01/01/2017, McMaster-Carr Commercial Company, Elmhurst. <https://www.mcmaster.com/>

**Figure 7:**

<b>Updated Contact List</b>			
Andrew Spencer	Steel Dynamics	260-868-8235	<a href="mailto:andrew.spencer@steeldynamics.com">andrew.spencer@steeldynamics.com</a>
Brent Walchuk	Steel Dynamics	248-290-6327	<a href="mailto:brent.walchuk@steeldynamics.com">brent.walchuk@steeldynamics.com</a>
Joel Grillo	Complete Drives Inc.	260-908-1882	<a href="mailto:jgrollo@completedrivesinc.com">jgrollo@completedrivesinc.com</a>
Tim Bosserman	Steel Dynamics	260-868-8000	<a href="mailto:tim.bosserman@steeldynamics.com">tim.bosserman@steeldynamics.com</a>
Tim Burkett	Steel Dynamics	260-868-8000	<a href="mailto:tim.burkett@steeldynamics.com">tim.burkett@steeldynamics.com</a>

Gantt chart:

Figure 8:



**Conclusions:**

The main goal for this job was to keep the system as robust and cost effective as possible. Once the first system is fully functioning then the three remaining hoppers will have the same system installed as well. If the design lasts over five years then SDI is strongly considering presenting the system to other SDI locations. SDI gave our group full authority to create the project and how to incorporate the opinions of electrical, mechanical and process engineers.



**COMPLETE DRIVES, INC.**  
 1542 AUBURN DRIVE  
 AUBURN, IN 46706

**QUOTE**

PHONE: 260-927-0328 FAX: 260-927-0329

Number	130814
Date	03/02/2017
Page	1

Ship To: SAME	STEEL DYNAMICS, INC 4500 CR 59 BUTLER, IN 46721	Bill To: 136S2	STEEL DYNAMICS, INC 4500 CR 59 BUTLER, IN 46721
------------------	---	-------------------	---

Reference #	Expires	Ship	Terms	W/	Freight	Ship Via
VERBAL KYLE	04/01/17	JG	2%-10 NET 30	02	PRE/ADD	DEL AUB JG

Quoted By:	JG	Quoted To:	KYLE MACKE
------------	----	------------	------------

Item	Description	Ordered	UM	Price	UM	Extension
60013-1-2	ENDURA MODEL 2500 2.5" PITCH LEAD TIME 6 WEEKS  *****CONVEYOR INFO***** FRAME CON. 10 GAUGE CONVEYOR LENGHT 15' 6" CHAIN STYLE 2.5" PITCH DOUBLE ROLLER CHAIN FLIGHTS 4" TAIL @ 10" CENTERS INFEED HEIGHT 30" TOF DISCHARGE HEIGHT 20" SUPPOTS CASTER DISCARGE END SUPPOTS REMOVED ON INFEED END DRIVE 1HP 460V 3PHASE DRIVE MOUNT SIDE MOUNT RIGHT HAND DRIVE LOCATED INFEED CONVEYOR SPEED 30FPM LIVE LOAD 2400 LBS CONTROLS START AND STOP INCLUDED FEATURES CHAIN COVERS AR PLATE BOTTOM PAN *****	1	EA	\$958.00	EA	\$958.00

Merchandise	Misc	Tax	Freight	Total
\$958.00	.00	.00	.00	\$958.00

\*\* WE APPRECIATE YOUR BUSINESS \*\*




Customer Copy

... Last Page

**PROPRIETARY INFORMATION**

THIS DRAWING IS THE CONFIDENTIAL PROPERTY OF ENDURA-VEYOR, INC. AND TRANSMITTED IN CONFIDENCE. THE PRODUCTION, USE OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN OR DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE EXPRESS WRITTEN PERMISSION OF ENDURA-VEYOR, INC.



- \*\*\*PLEASE SPECIFY\*\*\*
- RIGHT HAND DRIVE
  - OR
  - LEFT HAND DRIVE



NOTE:  
ALL BOTTOM PANS/DRAW SURFACES  
TO BE ABRASION RESISTANT STEEL

SIDE MOUNT DRIVE ASSEMBLY  
RIGHT HAND DRIVE SHOWN  
1HP-3PH-460V-TEFC  
AT 30 FPM FIXED

REMOVABLE TOP  
COVERS



**\*\*MAX LIVE LOAD = 950 POUNDS\*\***

PAINT COLOR:  
RAL-5019 CAPRI BLUE

**SAFETY REVIEW**

THE NEED FOR SAFETY DEVICES VARIES WITH EACH APPLICATION OF THIS EQUIPMENT. THIS DRAWING MAY NOT INCLUDE ALL APPROPRIATE SAFETY DEVICES FOR YOUR APPLICATION. AS SYSTEMS INTEGRATOR, PLEASE ADVISE YOUR CUSTOMER OF DEVICES THAT ARE APPROPRIATE FOR HIS/HER APPLICATION, BASED ON YOUR SAFETY ASSESSMENT. ADDITIONAL GUARDING, SAFETY CONTROLS, BARRICADES, END STOPS, ETC. COMPLIANCE WITH FEDERAL, STATE, OSHA AND LOCAL LAWS OR CODES ARE THE RESPONSIBILITY OF BOTH OF YOU, AS THE SYSTEMS INTEGRATOR/DISTRIBUTOR, AND THE END USER.

**APPLICATION REVIEW**

PLEASE REVIEW THE EQUIPMENT DESIGN FOR ITS ABILITY TO FUNCTION PROPERLY IN YOUR INTENDED APPLICATION. SYSTEM INTEGRATION AND APPLICATION REVIEW ARE NOT THE RESPONSIBILITY OF ENDURA-VEYOR INC. THEREFORE, ENDURA-VEYOR INC. MAKES NO CLAIMS AS TO THE PERFORMANCE OF THIS DESIGN FOR ANY PARTICULAR PURPOSE OR APPLICATION

APPROVED OR CHANGES AS SHOWN OR REQUIRED

CO. NAME \_\_\_\_\_

SIGNATURE \_\_\_\_\_

DATE \_\_\_\_\_



JOB NO: 89625

DRAWN BY: TEK

DATE: 4/6/2017

REVISION: --

SCALE: N/A REF JOB#:

DRG. NO:

89625 -

APPROVAL




TITLE: 2 1/2" P DRAG CHAIN FLIGHT CONVEYOR  
24" BW - 35 DEG. - "D"-STYLE

4

3

2

1



NOTE:

- BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED
- MCMasterCARR PART#: 1497K166

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES	
TOLERANCES:	
FRACTIONAL	
ANGULAR: MACH $\pm 1^\circ$	
TWO PLACE DECIMAL $\pm .01$	
THREE PLACE DECIMAL $\pm .005$	
FOUR PLACE DECIMAL $\pm .0005$	
INTERPRET GEOMETRIC TOLERANCING PER:	
MATERIAL	1045
FINISH	
DO NOT SCALE DRAWING	

DESIGN:	
DETAILED: JEDD MINNICH	
DATE: 3/15/2017	
ENG APPR.	
MFG APPR.	
Q.A.	

# ROTARY SHAFT

4

3

2

1

B

B

A





A

4

3

2

1



B

B

A

A

- NOTE:
- BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED
  - MCMasterCARR PART #: 7728T610

UNLESS OTHERWISE SPECIFIED:	DESIGN:	
DIMENSIONS ARE IN INCHES	DETAILED: J MINNICH	
TOLERANCES:	DATE: 3/15/2017	
FRACTIONAL	ENG APPR.	
ANGULAR: MACH ±1°	MFG APPR.	
TWO PLACE DECIMAL ±.01	Q.A.	
THREE PLACE DECIMAL ±.005		
FOUR PLACE DECIMAL ±.0005		
INTERPRET GEOMETRIC TOLERANCING PER:		
MATERIAL		
FINISH		
DO NOT SCALE DRAWING	<b>PILLOW BLOCK</b>	

4

3

2

1

4





3

2

1

B

B



A

A

4

3

2

1

NOTE:

- BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED
- McMASTERCARR PART#: 61005K960

UNLESS OTHERWISE SPECIFIED:	DESIGN: J MINNICH
DIMENSIONS ARE IN INCHES	DETAILED: J MINNICH
TOLERANCES:	DATE: 3/23/2017
FRACTIONAL	ENG APPR.
ANGULAR: MACH ±1°	MFG APPR.
TWO PLACE DECIMAL ±.01	
THREE PLACE DECIMAL ±.005	
FOUR PLACE DECIMAL ±.0005	
INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.
MATERIAL:	
FINISH:	
DO NOT SCALE DRAWING	



61005K960

4

3



2

1



SECTION A-A

SCALE 1 : 10



ITEM NO.	PART NUMBER	QTY.
1	HOUSING	1
2	PADDLE ASSEMBLY	1
3	61005K96	1
4	7728T61	2
5	1497K166	1
6	GR-HMQ842-XX-H2-56-23	1
7	9414T27	1
8	GUARD	1

B

B

A

A

NOTE:  
 • BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ANGULAR: MACH ±1° TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 FOUR PLACE DECIMAL ±.0005	DESIGN: J MINNICH DETAILED: J MINNICH DATE: 3/23/2017 ENG APPR. MFG APPR.	
INTERPRET GEOMETRIC TOLERANCING PER: MATERIAL HRS		
FINISH		
DO NOT SCALE DRAWING		

HOUSING\_END

4

3

2



1

4


3

2

1



4 x  $\phi$  0.531 THRU ALL  
 $\square$   $\phi$  0.813  $\nabla$  0.500  
 $\surd$   $\phi$  0.863 X 90°, Near Side  
 $\surd$   $\phi$  0.581 X 90°, Far Side



NOTE:  
 • BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:	DESIGN: J MINNICH	
DIMENSIONS ARE IN INCHES	DETAILED: J MINNICH	
TOLERANCES:	DATE: 3/23/2017	
FRACTIONAL	ENG APPR.	
ANGULAR: MACH $\pm$ 1°	MFG APPR.	
TWO PLACE DECIMAL $\pm$ .01	Q.A.	
THREE PLACE DECIMAL $\pm$ .005		
FOUR PLACE DECIMAL $\pm$ .0005		
INTERPRET GEOMETRIC TOLERANCING PER:		
MATERIAL TOOL STEEL	<b>CUTTING EDGE</b>	
FINISH		
DO NOT SCALE DRAWING		

4

3

2

1

B

B

A




A

4

3

2

1



B

B

A

A

- NOTE:
- BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED
  - PURCHASE SHAFT COLLAR.
  - McMASTERCARR PART# : 9414T27


UNLESS OTHERWISE SPECIFIED:	DESIGN: J MINNICH	
DIMENSIONS ARE IN INCHES	DETAILED: J MINNICH	
TOLERANCES:		
FRACTIONAL	DATE: 3/23/2017	
ANGULAR: MACH±1°	ENG APPR.	
TWO PLACE DECIMAL ±.01	MFG APPR.	
THREE PLACE DECIMAL ±.005		
FOUR PLACE DECIMAL ±.0005		
INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.	
MATERIAL	FLAG	
FINISH		
DO NOT SCALE DRAWING		

4

3

2


1



ITEM NO.	PART NUMBER	QTY.
1	HOUSING_BACK	1
2	HOUSING_END	2
3	HOUSING_FRONT	1
4	CUTTING EDGE	1
5	HX-SHCS 0.5-13x0.75x0.75-C	6
6	HX-SHCS 0.5-13x1.25x1.25-C	4

NOTE:  
 • BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ANGULAR: MACH±1° TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 FOUR PLACE DECIMAL ±.0005	DESIGN: J MINNICH	
	DATE: 3/23/2017	
	ENG APPR.	
	MFG APPR.	
INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.	
MATERIAL: STEEL	<b>HOUSING</b>	
FINISH:		
DO NOT SCALE DRAWING		



NOTE:

- USE 14" SCHEDULE 80 STEEL PIPE FOR RADIUS.
- BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:	DESIGN: J MINNICH	
DIMENSIONS ARE IN INCHES	DETAILED: J MINNICH	
TOLERANCES:	DATE: 3/23/2017	
FRACTIONAL	ENG APPR.	
ANGULAR: MACH ±1°	MFG APPR.	
TWO PLACE DECIMAL ±.01		
THREE PLACE DECIMAL ±.005		
FOUR PLACE DECIMAL ±.0005		
INTERPRET GEOMETRIC TOLERANCING PER:		
MATERIAL		
FRSH		
DO NOT SCALE DRAWING		

HOUSING\_BACK

4

3

2




1

B

B

A

A



NOTE:  
 • BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:	DESIGN: J MINNICH	
DIMENSIONS ARE IN INCHES	DATE: 3/23/2017	
TOLERANCES:	ENG APPR.	
FRACTIONAL	MFG APPR.	
ANGULAR: MACH±1°	Q.A.	
TWO PLACE DECIMAL ±.01		
THREE PLACE DECIMAL ±.005		
FOUR PLACE DECIMAL ±.0005		
INTERPRET GEOMETRIC TOLERANCING PER:		
MATERIAL		
FRSH		
DO NOT SCALE DRAWING		
	<b>HOUSING_END</b>	

4

3

2


1

4



3

2

1



6 x  $\phi$  0.531 THRU ALL  
 ✓  $\phi$  0.580 X 90°, Near Side  
 ✓  $\phi$  0.580 X 90°, Far Side



B

B

A

A

NOTE:  
 • USE 14" SCHEDULE 80 STEEL PIPE FOR RADIUS.  
 • BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:	DESIGN: J MINNICH	
DIMENSIONS ARE IN INCHES	DETAILED: J MINNICH	
TOLERANCES:	DATE: 3/23/2017	
FRACTIONAL	ENG APPR.	
ANGULAR: MACH $\pm 1^\circ$	MFG APPR.	
TWO PLACE DECIMAL $\pm .01$	Q.A.	
THREE PLACE DECIMAL $\pm .005$		
FOUR PLACE DECIMAL $\pm .0005$		
INTERPRET GEOMETRIC TOLERANCING PER:		
MATERIAL		
FINISH		
DO NOT SCALE DRAWING		

HOUSING\_FRONT

4

3

2

1

4


3

2


1

B

B



20X  $\phi$  0.313 THRU ALL  
 3/8-16 UNC THRU ALL  
 $\checkmark$   $\phi$  0.425 X 90°, Near Side  
 $\checkmark$   $\phi$  0.425 X 90°, Far Side



A

A

0.510

NOTE:  
 • BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:  
 DIMENSIONS ARE IN INCHES  
 TOLERANCES:  
 FRACTIONAL  
 ANGULAR: MACH  $\pm 1^\circ$   
 TWO PLACE DECIMAL  $\pm .01$   
 THREE PLACE DECIMAL  $\pm .005$   
 FOUR PLACE DECIMAL  $\pm .0005$

INTERPRET GEOMETRIC  
 TOLERANCING PER:

MATERIAL

HRS

FINISH

DO NOT SCALE DRAWING

DESIGN: J MINNICH

DETAILED: J MINNICH

DATE: 3/23/2017

ENG APPR.

MFG APPR.

Q.A.

PADDLE

4

3

2




1

4

3

2

1



SECTION B-B

SCALE 1:5

ITEM NO.	PART NUMBER	QTY.
1	PADDLE	2
2	WEAR BAR	4
3	PADDLE_END	2
4	1497K166	2
5	91253A624	40

UNLESS OTHERWISE SPECIFIED:  
 DIMENSIONS ARE IN INCHES  
 TOLERANCES:  
 FRACTIONAL  
 ANGULAR: MACH±1°  
 TWO PLACE DECIMAL ±.01  
 THREE PLACE DECIMAL ±.005  
 FOUR PLACE DECIMAL ±.0005  
 INTERPRET GEOMETRIC  
 TOLERANCING PER:  
 MATERIAL HRS  
 FINISH  
 DO NOT SCALE DRAWING

DESIGN: J MINNICH

DETAILED: J MINNICH

DATE: 3/23/2017

ENG APPR.

MFG APPR.

Q.A.

NOTE:  
 • BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

PADDLE\_ASSEMBLY

4

3

2

1

B

B

A

A

4



3

2

1


B

B



A

A



$\phi 1.435 -0.003 \nabla 0.375$

NOTE:  
 • BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:	DESIGN: J MINNICH	
DIMENSIONS ARE IN INCHES	DATE: 3/23/2017	
TOLERANCES:	ENG APPR.	
FRACTIONAL	MFG APPR.	
ANGULAR: MACH±1°	Q.A.	
TWO PLACE DECIMAL ±.01		
THREE PLACE DECIMAL ±.005		
FOUR PLACE DECIMAL ±.0005		
INTERPRET GEOMETRIC TOLERANCING PER:		
MATERIAL		
FRSH		
DO NOT SCALE DRAWING		
	<b>PADDLE_END</b>	

4

3

2




1

4

3

2

1



- NOTE:
- BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED
  - USE 20 GAUGE SHEET METAL FOR GUARD

UNLESS OTHERWISE SPECIFIED:	DESIGN: J MINNICH	
DIMENSIONS ARE IN INCHES	DETAILED: JEDD MINNICH	
TOLERANCES:	DATE: 3/15/2017	
FRACTIONAL	ENG APPR.	
ANGULAR: MACH ±1°	MFG APPR.	
TWO PLACE DECIMAL ±.01		
THREE PLACE DECIMAL ±.005		
FOUR PLACE DECIMAL ±.0005		
INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.	
MATERIAL	<b>SHAFT GUARD</b>	
FINISH		
DO NOT SCALE DRAWING		

4

3

2

1

B

B

A




A

4

3

2

1



NOTE:  
• BREAK ALL SHARP EDGES UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES	
TOLERANCES:	
FRACTIONAL	
ANGULAR: MACH ±1°	
TWO PLACE DECIMAL	±.01
THREE PLACE DECIMAL	±.005
FOUR PLACE DECIMAL	±.0005
INTERPRET GEOMETRIC TOLERANCING PER:	
MATERIAL	HRS
FINISH	
DO NOT SCALE DRAWING	

DESIGN: J MINNICH
DATE: 3/23/2017
ENG APPR.
MFG APPR.
Q.A.

WEAR BAR

4

3

2

1

B

B

A

A


## IRONMAN GR Series

[ADD TO CART](#)
[BACK TO SELECTOR](#)

### General Information

Model Number	GR-H1M0842-100-H2-56-23
Unique Part Number	GR8420884.23
Product Family	GR
Weight (lbs.)	149

\*Please contact your local sales representative for final pricing.



H2



### Product Specifications

Ratio:1	100
Input RPM	1750
Output RPM	17.5
Input HP	1.201
Output HP	0.792
Output Torque (lb.-in.)	2852
Housing Construction	Cast Iron 800 Worm Gear Reducers
Overhung Load (lbs.)	3750
Reducer Type	Worm - Right Angle
Center Distance (in)	4.25
Input Style	Motorized, Quill Input
Frame Size	56
Output Orientation	H2
Output Shaft Assembly	Hollow Shaft
Bore Size (in)	1.438

\* Service Factor of 1.0, dependent upon application

Confirm motor power ratings do not exceed gearbox power ratings

Others Chose . . .



CONT. ON SH.


CUSTOMER:		DIS.		A. REV.		SERIES	
PROJECT: STEEL DRUMS TWIN-SHELL CR/11/12		A. REV.		A. REV.		SERIES	
SECTION: CR CONTROL POWER DISTRIBUTION		CUSTOMER Dwg No.				SERIES	
TITLE:						DRAWN:	
FILE NAME:							

A B C D E F G H J K L M N P Q R S

01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95

34 78

CONT. ON SL



Cycle Complete



Cycle Start



E-STOP

14X14  
Hoffman  
Enclosure

CUSTOMER:		DES:	Δ REV.	Δ REV.	SHEET
PROJECT: SILE DRUMS TR-S&L C/14R		Δ REV.	Δ REV.	Δ REV.	Δ REV.
SECTION:		CUSTOMER DWG No.			
TITLE: BR CONSOLE PANEL ENCLOSURE					
FILE NAME					